

RESPONSECARD® LT

ResponseCard LT is the latest cost-effective clicker. LT utilizes the same, reliable radio frequency technology as standard clickers, but has been reengineered to incorporate cost reductions that ensure reliability of response transmission in a durable, compact case.

Optimized for any size presentation environment, ResponseCard LT operates on patented two-way RF technology. An LED light on the clicker indicates that responses have been received. ResponseCard LT features a simple, five button input to facilitate easy participant responding. Its compact size makes LT easy to transport and equip in any environment.



SPECS

SIZE & WEIGHT

Height: 2.9 inches (74 mm)
Width: 1.8 inches (45 mm)
Depth: 0.28 inches (7 mm)
Weight: 0.7 ounce (19.8 grams)

RANGE

200' radius (400' coverage)

BATTERY & POWER

1 coin cell CR2032

INPUT DEVICE CAPABILITY

6 keys (1/A - 5/E, Ch)
Programmable with ResponseCard Programmer

USER IDENTIFICATION

Select a channel in less than five seconds, indicating session choice
Select a channel anytime - even when a session is underway
Channel selection is preserved until changed by participant

DISPLAY

LED Light. Participants receive answer confirmation on ResponseCard through two-way communication. Successful transmissions are acknowledged on the participant's keypad via three second green light signal.

RF TECHNOLOGY

25 Channels
Fully FCC, CE and Industry Canada certified
Will not interfere with other technologies
Not limited to line-of-sight transmission
Ability to prohibit participants from channel changing

RECEIVER COMPATIBILITY

RF+ Receiver (RRRF-03)
RF Receiver (RRRF-04)