



## Versatile Portable Projector with High Brightness

### FEATURES

- DLP® technology with BrilliantColor™ for vibrant and rich picture quality
- Short throw lens delivers 100" image at only 1.3m away
- 3,200 ANSI lumens of brightness and 15,000:1 contrast ratio for clear, crisp and bright presentations
- XGA (1024 x 728) native resolution and support up to maximum WUXGA (1920x1200) resolution
- Dual-HDMI inputs for high definition content with the same high quality
- Compact and lightweight at 2.6kg for easy portability
- A long lamp life up to 10,000 hours for low Total Cost of Ownership (TCO)
- Audio ready with built-in 2 watt audio speaker, audio-in and audio-out ports



## Short throw lens delivers 100" image at only 1.3m away

The DX281-ST projector delivers a 100" diagonal image at only 1.3 meters projection distance. With a brightness of 3,200 ANSI Lumens and contrast ratio of 15,000:1 it delivers a perfect image display. With its light weight and compact form this is a short throw projector for easy installation that will fit any budget.



## DX281-ST SPECIFICATIONS

Image	<b>Display Type</b>	Single chip DLP® Technology by Texas Instruments
	<b>Brightness</b>	3200
	<b>Native Resolution</b>	XGA (1024 x 768)
	<b>Max. Supported Resolution</b>	WUXGA (1920 x1200) @60Hz
	<b>Native Aspect Ratio</b>	4:3
	<b>Contrast Ratio</b>	15,000:1
	<b>Keystone Correction</b>	Vertical: +/-40°
Optical	<b>Throw Ratio</b>	0.63 : 1
	<b>Zoom Ratio</b>	1x
	<b>Image Size (Diagonal)</b>	56" - 120"
	<b>Projection Distance</b>	54 - 154 cm
	<b>Projection Lens</b>	F = 2.7, f = 7.2 mm
Features	<b>Features</b>	3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), 3D Mandatory Formats supported (top/bottom, right/left, frame sequential)
Connectivity	<b>I/O Connection Ports</b>	VGA-In (15pin D-Sub) (x2), HDMI (x2), S-Video, Composite Video, Audio-In (Mini-Jack), VGA-Out (15pin D-Sub), Audio-Out (Mini-Jack), RS-232, USB miniB (Service)
General	<b>Dimensions (W x D x H)</b>	332 x 243.6 x 107 mm
	<b>Weight</b>	2.6
	<b>Lamp Life and Type</b>	5,000 / 7,000 / 10,000 Hours (Normal / Eco. / Dynamic Eco. Mode), 203W
	<b>Speakers</b>	2W
	<b>Standard Accessories</b>	VGA Cable, User Manual (CD), Quick Start Guide, Warranty Card (by region), Remote Controller (with battery), AC Power Cord
	<b>Optional Accessories</b>	Spare Lamp P/N (XX5050002200), Remote Control P/N (XX5040005400), Carrying Case P/N (XX3520000800)
	<b>Warranty</b>	Entry Warranty: 2 years projector / 1 year on lamp or 1.000 hours whichever comes first
	<b>UPC Code</b>	813097023353